

Index protection
IP54 (IP20 superior)

Colour temp.
2700K + 3000K + 4000K

Flicker
<7%

Technology
LED

Step McAdam
4-SDCM

Guarantee
5 years

Driver
Included

Class
II

CRI
80

Voltage
230V


Lifetime
65.000h L80B10




Holp

Compact downlight with slightly recessed textured opal diffuser that generates a pleasant lighting effect, also adjustable in colour temperature (3CCT). Ideal for installation in spaces with little recessing space thanks to its minimal height.

01845-
Holp S




Ø111 mm




Cut-out 90mm

52 mm

01855-
Holp M




Ø146 mm




Cut-out 120mm

52 mm

01875-
Holp L



Ø226 mm



Cut-out 200mm

52 mm


	Colour	CRI/Temp.	Angle	Led	Dimming	Emergency
01845-	0 White	S 80 /	9 100°	0 750 lm / 6W	- On-Off	EM Ki 1h
	1 Black	27-30-40K			D Dali push	
					R Edge cut	

	Colour	CRI/Temp.	Angle	Led	Dimming	Emergency
01855-	0 White	S 80 /	9 100°	0 1200 lm / 9W	- On-Off	EM Ki 1h
	1 Black	27-30-40K			D Dali push	
					R Edge cut	


	Colour	CRI/Temp.	Angle	Led	Dimming	Emergency
01875-	0 White	S 80 /	9 100°	0 2950 lm / 21W	- On-Off	EM Ki 1h
	1 Black	27-30-40K			D Dali push	
					R Edge cut	

Holp Deep

01846-
Holp S Deep




Ø111 mm




Cut-out 90mm

72 mm

01856-
Holp M Deep




Ø146 mm




Cut-out 120mm

87 mm

01876-
Holp L Deep



Ø226 mm



Cut-out 200mm

87 mm

	Colour	CRI/Temp.	Angle	Led	Dimming	Emergency
01846-	0 White	S 80 /	9 100°	0 750 lm / 6W	- On-Off	EM Ki 1h
	1 Black	27-30-40K			D Dali push	
					R Edge cut	

	Colour	CRI/Temp.	Angle	Led	Dimming	Emergency
01856-	0 White	S 80 /	9 100°	0 1200 lm / 9W	- On-Off	EM Ki 1h
	1 Black	27-30-40K			D Dali push	
					R Edge cut	

	Colour	CRI/Temp.	Angle	Led	Dimming	Emergency
01876-	0 White	S 80 /	9 100°	0 2950 lm / 21W	- On-Off	EM Ki 1h
	1 Black	27-30-40K			D Dali push	
					R Edge cut	

