



PIXEL

EN

This panel has been designed

technology that guarantees the non-yellowing of the diffuser.

Thanks to the technology used, we achieve total control of light

for people exposed to artificial lighting (up to flicker < 1%). This fixture can be controlled by Dali and Bluetooth.

Technical information

Impact Protection	IP20
UGR:	<19 **
Driver:	Included/ Incluido
CRI:	>80
Temperature	3000K/4000K
Lifetime	50.000 h licker < 1%
Technology	LED
Guarantee	5 years / 5 años
Class	II
Voltage	230V
Step McAdam:	3-SDCM
Bluetooth:	>20m
Flicker:	Flicker Free

14221E



Model:

	Colour	CRI/Temp.	Angle	Led	Dimming	Emergency
14221-	0 White	C 830	9 120°	5* 3800 lm / 30W	- On-Off	- No emergency
		N 840		6 4800 lm / 40W	D Dali	EM 1H Kit
	T* 827-865			B Bluetooth		
				Z Zigbee		
				N Dali no push		

Accessories

17941-0	White ceiling base 1500mm 3 wire
17942-0	White ceiling base 1500mm 5 wires (DALI)
14290-	1500mm suspension cable (4 pcs.)
1429 2-	False ceiling anchor kit Grill
14293-	Canopy suspension kit 3 wires + 4 steel cables

14294-0	Surface adapter frame white 600x600x70mm
---------	--



Quality certificates:

